Rc Hobby wifi Receiver CTW-022

Control distance Outdoor:80M Indoor Control distance ☐50M

Specification:

A Wi-Fi receiver for the $7.2V \sim 9.6V$ electric power RC models which has independent ESC and servo. 2.4G (802.11n) and 5G (802.11a) dual-band switch on board, so if using 802.11a supported iOS devices, the great advantage is there will be no 2.4G signal interfering.

2 dual-band Wi-Fi antennas.

Camera vertical view angle to be controlled remotely.

Real-time video transmission with 640x480 for iPad and 320x240 for iPhone/iPod-touch.

Photo taking and stored into iOS system library. (Allowed to synchronized to PC via iTune)

Replaceable horn sound, allow 5 seconds self-recorded voice as the replacement.

Built-in MIC and Speaker for 2-way real-time audio communication, adjustable Speaker volume.

One LEDs to indicate the FUNGuider is ready for connection (blinking) or connected (steady).

Including:

- 1 * 2.4G/5G Dual-band Collapsible antenna
- 2 * Signal extension cord
- 1 * T- plug adapter cable plus JST plug adapter cable
- 1 * Big Tamiya adapter cable plus JST plug adapter cable
- 1 * Small Tamiya adapter cable plus JST plug adapter cable
- 1 * User's manual
- 1 * The black EVA sponge pad (thickness:2.5cm Size: 100*55*25mm)
- 1 * The black EVA sponge pad (thickness:4cm Size: 100*55*40mm)
- 1 * The black EVA sided glue(Size: 100*20*3mm)
- 1 * Color box

CHINA TOPWIN INDUSTRY CO.,LTD

 $ADD: B-C\ of\ 3/F, Block\ B, CENTRAL\ Building, Xixiang\ Road, BaoAn\ District, Shenzhen, China$

Tel:86-755-83660365 83660404 E-mail:sales@chinatopwin.com Fax:86-755-83660251 Website:www.chinatopwin.com